



The IP Transceiver transmits Video, Audio and Control Data within a Network-based OR Infrastructure

Lossless Transmission

TIP0410 transmits data up to 4K UHD resolution at a frame rate of 30 Hz (up to 60 Hz with full HD resolution) with speeds as high as 10 Gbps. The device achieves this without compression and fully retains the color space, ensuring optimum image quality.

Instantaneous Image Viewing

Images are transmitted without any visual delay, offering a seamless hand-eye coordination experience for the attending physician. He/she receives direct visual response to his/her actions, for example during endoscopic interventions.



TIP0410

Extensive Transmission Distance

Data is transmitted via fiber-optic cable, enabling transmission distances of up to 10 kilometers. As a result, not only separate rooms, but entire buildings can be linked to one another, with image data and audio seamlessly transmitted between them. This is useful for transmitting data within and outside of the OR, as well as to conference rooms, lecture halls, and other locations.

Universal Application

The TIP0410 can be used simultaneously as an encoder and decoder. This simplifies installation and saves on time and labor costs associated with storage and maintenance of the entire system.

Two Signals Simultaneously

Up to two video links can be processed concurrently with one TIP0410. At the same time, a video signal can be fed in via the HDMI input in the network and another signal can output from the network via one of the two HDMI outputs. With a connected full HD signal, this can also be looped through to one of the HDMI outputs.

Remote Operation Possible

IP-based data transmission enables the use of the same network cables for the transmission of all information, whether image, audio, video, or control of a keyboard and mouse. For example, a computer in a remote computing center can be operating via the EIZO system directly from OR.

Integrated Video Management

Various video sources can be displayed simultaneously on a screen using a single cable to enable various multiple views.

Passive Cooling

TIP0410 implements passive cooling for noiseless operation and minimal mechanical wear. This also eliminates any interference with the laminar flow in the OR to prevent unwanted movement of dust particles and bacteria.


Integration into Existing Systems

TIP0410 is compatible with a wide assortment of commercially-available network components and can be integrated seamlessly into existing systems and applications.


Specifications

Cabinet Color		Silver
Network	Data Rate	10 Gbit/s
	Connector	SFP+ (10 GbE, optional SFP+ module)
	Cable	LWL duplex LC/LC (SFP+ module necessary)
Video	Input Resolution	Up to FHD (1920 x 1080) and WUXGA (1920 x 1200), 1 x uncompressed, 60 Hz and 30 Hz, progressive and interlaced Up to 4K (3840 x 2160), 1 x uncompressed, 30 Hz
	Output Resolution	Up to FHD (1920 x 1080) and WUXGA (1920 x 1200), 2 x uncompressed, 60 Hz and 30 Hz, progressive Up to 4K (3840 x 2160), 1 x uncompressed, 30 Hz
	Interface	HDMI 1.4 (in), HDMI 1.4 x 2 (out)
	Modes	Single In / Single Out (up to 4K/30Hz) In/Out (up to 4K/30Hz) Dual Out (up to FHD) Loop Through (up to 4K/30Hz)
Multiview	Side-by-Side, Picture-in-Picture, QuadView, Matrix View 3+1 and 1+3 right	
Connectors	Audio	Audio jack x 2 (in/out)
	USB Ports	USB/A x 2, USB/B
Control	Mouse and keyboard control	
Services	Remote diagnosis, remote firmware update	
Power Consumption	17 W, optional: 5 W (for USB), passive cooling	
Power Requirements	External power supply, 230 AC	
Net Weight	1050 g	
Certifications & Standards (Please contact EIZO for latest information)	CE / UKCA, IEC/EN 62368-1, testet for IEC60601-1-2, RoHS, Reach, WEEE	
Optional Accessories	Optical module (SFP+ 10G LC), power supply, connecting and mounting accessories	

Dimensions (mm)



Connectors



You will find your EIZO contact partner at:
<https://eizo-or.com/contact>

EIZO, the EIZO logo, and CuratOR are registered trademarks of EIZO Corporation in Japan and other countries. VESA is a registered trademark of Video Electronics Standards Association. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI logo are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and other countries. All other company names, product names, and logos are trademarks or registered trademarks of their respective owners. Specifications are subject to change without notice.